

SATELLINE® -3AS(d) NMS

Wireless World – Local Solution

The SATELLINE-3AS NMS introduces SATEL's concept of remotely manageable radio modems. In addition to ordinary communication functions, it offers configuration through radio, efficient diagnostics tools and accumulation of operation statistics data.

The management and surveillance of a network of 3AS NMS radio modems is effected through the Master Station connected by a serial interface to a PC with dedicated Network Management software. The user data and NMS information are transferred seamlessly together. The Network Management System is compatible with most user protocols, making the NMS network suitable for a wide range of applications.

VHF with NMS

UHF with NMS

UHF

Licence Free

IP67

OEM



With SATEL radio modems, setting up a local data transfer network is quick and cost effective. Your wireless network is independent and free of operator services. The cost of operation is either free of charge or fixed, depending on the frequency used. SATELLINE radio modems are type-approved in over 50 countries. For the latest information, please visit our website www.satel.com.

SATELLINE radio modems are always on line, and provide reliable, real-time data communications over distances ranging from tens or hundreds of metres up to around 80 kilometres. Thanks to a store and forward function, any radio modem in a network can be used as a master station, substation and / or repeater.

SATELLINE radio modem networks are flexible, easy to expand and can cover a wide variety of solutions from simple point-to-point connections to large networks comprising hundreds of modems. Even for expanded networks, only one operating frequency is required.

All SATELLINE radio data modems fulfil RoHS requirements (EU directives 2002/95/EC and 2002/96/EU) as of 1 July 2006.



A SATELLINE-3AS(d) NMS network consists of remotely adjustable radio modems operated in a polling mode and controlled through the Master Station by dedicated SATEL NMS PC software. The SATEL NMS PC software provides the user with a powerful graphical tool for designing a radio network, which ensures that each NMS radio modem receives and transfers only the messages intended for it, and that each message is appropriately routed, using repeaters where necessary.

Reliability and Efficiency

The Network Management System provides remote configuration of the network and advance indication of faults, for maximum reliability, labour-saving maintenance work and efficient system management.

The NMS radio modems monitor, on a continuous basis, the condition of the radio connection, in particular the strength of the signal (RSSI) and the voltage level of the power source as well as the inside temperature of the modem. The information is transmitted to the SATEL NMS PC software, where it is stored and displayed as logs and trend data. With the help of the graphical display of the network available at the SATEL NMS PC software, the user can conveniently configure, add or remove radio modems as well as set repeater links, without the need of a terminal.

The Network Management System benefits the user in several ways, including

- Enhanced reliability, through advance indication of anticipated faults and failures
- Reduced configuration and maintenance costs, through remote configuration
- An efficient tool for network development

Expert's help always at hand

With over 20 years of experience, SATEL Oy has grown into one of the leading radio modem manufacturers in the world. As a result of our persistent and innovative work in both product design and international marketing, we now offer an extremely large selection of radio modems, and operate through an extensive and skilled distributor network all over the world.

SATEL Oy is an ISO 9001:2008 and ISO 14001:2004 certified company. The quality of our operations and products is kept as flawless and at as high level as possible.

We have also accumulated a considerable amount of know-how in different radio modem applications. So, whatever your application is, do not hesitate to ask for our expert help whenever you need it. SATELLINE radio modems have been used, for example, at airports, waterworks and electricity plants for various monitoring and control applications, as well as to set up location data-based fleet management systems in cities.

SATEL Oy has prepared an extensive set of Application Notes describing the different ways of utilising SATEL radio modems in various applications. For further information about our products and their applications, please visit our home page www.satel.com or contact your local dealer.

Manufacturer:



SATEL Oy,
Meriniitynkatu 17, P.O. Box 142,
FI-24101 Salo, FINLAND

Tel. +358 2 777 7800 info@satel.com
Fax +358 2 777 7810 www.satel.com

Technical Specifications SATELLINE-3AS(d) NMS

The equipment complies with the EN 300 113-1, -2, EN 301 489-1, -5, IEC 60950 and FCC CFR47 part 90 specifications. In addition it meets the EN 300 220-1, -3 with 25 kHz channel spacing.

TRANSCEIVER

Frequency Range	330...470 MHz
Tuning Range	+/- 2 MHz from central frequency
Channel Spacing	12.5 kHz / 20 kHz / 25 kHz
Number of Channels	160 / 100 / 80 (or 2 x 160 / 100 / 80) *Note1
Frequency stability	< ± 1.5 kHz
Type of Emission	F1D
Communication Mode	Half-Duplex

TRANSMITTER

Carrier Power	10 mW...1 W / 50 ohm
Carrier Power Stability	+ 2 dB / - 3 dB
Adjacent Channel Power	according to EN 300 220-1 / EN 300 113-1
Spurious Radiation	according to EN 300 220-1 / EN 300 113-1

RECEIVER

Sensitivity	< -115 dBm (BER < 10 E-3) *Note2
Co-channel Rejection	> -12 dB
Adjacent Channel Selectivity	> 60 dB @ 12.5 and 20 kHz / > 70 dB @ 25 kHz
Intermodulation Attenuation	> 65 dB
Spurious Radiation	< 2 nW

DATA MODEM

Interface level	RS-232, RS-485 or RS-422
Interface	One port for data and one for NMS
Interface Connector	D15, female
Data speed of RS interface	1200 - 38400 bps
Data speed of radio interface	19200 bps @ 25 kHz, 9600 bps @ 12.5 / 20 kHz
Data format	Asynchronous RS-232, RS-422, RS-485

GENERAL

Operating voltage	+ 9 ... + 30 Vdc
Power consumption (average)	1.4 W typical (Receive) 6.0 W typical (Transmit) 0.05 W typical (in Standby mode)
Temperature range - Operating	-25 °C...+55 °C (tests acc. to ETSI standards)
	-40 °C ... +75 °C (absolute minimum / maximum)
- Storage	-40 °C ... +85 °C
Antenna Connector	TNC, 50 ohm, female
Construction	Aluminium Enclosure
Size H x W x D	137 x 67 x 29 mm
Installation plate	130 x 63 x 1 mm
Weight	260 g
MTBF	60 years

Values are subject to change without notice.

*Note1: The Dual Band version operates on two separate 2 MHz frequency bands.

*Note2: Depending on Receiver settings.

Distributor: