

**CHALLENGE.
SOLUTION.
SUCCESS.**

26
PRODUCT
CATALOGUE



**High-quality radio
technology for
real-time wireless
data communication.**

SATEL

Mission-Critical Connectivity

SOLVING YOUR CHALLENGES

SATEL is a trusted wireless technology expert and innovator who develops and sells high quality connectivity solutions.

Our solutions are used in a wide range of industrial applications enabling secure, mission-critical connections. All SATEL products are designed and manufactured in Finland.

Reliable connections, protected business

SATEL technology is easy and fast to implement and use with low life cycle costs. Our solutions are expandable, customizable, flexible and secure.

You get added value from our services. We offer network design and technical support, and we have a wide distributor network at your service.



Expertise
High quality
Operational security
Independence

Easy implementation
Low life cycle costs
Service and support
Global distribution network



SUSTAINABILITY AS A CORE VALUE

- SATEL is committed to carrying out its business in a sustainable way.
- Our radio technology is designed, manufactured and tested in Finland.
- We have a long tradition of environmentally friendly practices, and we perform highly in ESG (Environmental, Social and Governance) criteria.

SATEL radio technology can be used in various mission-critical applications such as SCADA, machine control, smart farming, ITS, autonomous vehicles, GNSS, offshore, environmental monitoring and Industrial Internet. Mission-critical nature of these applications calls for very tight requirements for connectivity, reliability, accuracy and security. Many of the applications that use radio connectivity solutions make operations safer and more sustainable.



APPLICATIONS

SATEL's technology is used globally in a wide range of industrial applications that require the utmost reliability and security. The application possibilities are numerous.

MACHINE CONTROL

Modern construction machinery transfer data from/to cloud environment to ensure efficient and safer worksite, and enable accurate workflow.

Machine control requires accurate position based on design models and plans. SATEL's connectivity technology is perfect for mission-critical operations in harsh extreme areas, even in areas with limited network coverage or no coverage at all.

With machine control operations become easier and more sustainable. Environmental impact is manifested in lower fuel consumption and CO₂ emissions, and longer machine lifecycle. For example, in precision farming, the use of seeds, fertilizers and pesticides becomes more accurate.



ITS

Intelligent Transport Systems are improving travel experience everywhere, and operational communication is a major factor in this. Private radio data network ensures the functionality of these applications. SATEL's radio technology is used in public transport e.g. in traffic light and traffic sign control, real-time passenger information systems and automatic vehicle location.

In ITS radio technology contributes to making transportation more efficient, environmentally friendly and safe. The results can be seen in reduced driving times, less fuel consumption and less CO₂ emissions.



ENVIRONMENTAL MONITORING

Wireless radio technology is one key aspect in Environmental Monitoring. It brings safety, operability and control. With SATEL's solutions you can monitor weather conditions and get information for example in flood, fire or drought situation. They provide real-time information of environmental conditions without additional costs and with a minimum supervision.



TELEMETRY

Telemetry refers to the process of collecting and transmitting data from remote or inaccessible sources to a central location for monitoring, analysis, and decision-making. This data can include various measurements, such as temperature, pressure, speed, location, or any other relevant parameter depending on the application.

SATEL's solutions provide real-time data from remote locations, and improve efficiency and safety in mobile or temporary telemetry applications. High-quality radio technology is reliable even in the most difficult environments, such as hot desert or icy arctic conditions.



UTILITIES

Utility systems require a highly reliable monitoring and controlling network. Malfunctions should be pinpointed quickly and even restored remotely. SATEL offers comprehensive solutions that are easy to implement and expand. SATEL radio technology is currently being used e.g. in power distribution, advanced metering infrastructure, windmills, waterworks, sewer networks, district heating and gas pipelines.

In utility communications, real-time wireless monitoring and remote access add efficiency and support interference-free operation, cut reaction times and minimize the environmental impact, for example water losses.



OEM

SATEL have produced a range of OEM radio modules for system manufacturers to integrate into customer solutions. They are secure, customizable and flexible in mounting options. SATEL's solutions are widely compatible and also support other manufacturers' radio protocols.



DEFENSE

Defense forces all around the world use lot of time and money for practicing. To get the most out of the investment and to guarantee the quality and safety, practices are monitored in real-time and the results are analyzed for further development.

SATEL's radio technology is used for example in target practice on land, at sea, and in the air. SATEL products can be used to transmit location and telemetry data from a moving target to the operator reliably, even over long distances.



SATEL MCCU

The MCCU (Mission-Critical Connectivity Unit) platform is designed to resolve connectivity challenges in harsh environments. It delivers mission-critical signaling from relatively small machine control messages with constant latency to wideband and low latency camera stream.

SATEL focuses on mission-critical connectivity applications by intelligently and smartly combining multiple wireless technologies. The machine and vehicle manufacturers, and machine control system providers can integrate SATEL MCCU into their offering without knowing what kind of technology is available in the operating area. The vehicle can be operated under varying connectivity environments.

SATEL MCCU-30

The SATEL MCCU-30 is a versatile, innovative, and robust multi-band vehicle router solution that effectively tackles connectivity challenges in a wide range of applications, including machine control and off-highway vehicles.

It excels in providing reliable connectivity by smartly integrating various wireless technologies to tackle even the most intricate scenarios, all within a single unit. Whether you are dealing with a new build or retrofit projects, SATEL MCCU-30 offers adaptability, thanks to its field proven and IP classified mechanics.


SATEL MCCU-30 is designed to resolve various connectivity challenges in harsh environments:

- LTE, Wi-Fi, UHF, BT (all can be used simultaneously)
- Based on field proven mechanics
- IP67 / IP69K classification
- Vibration, shock and temperature
- Connections with surge and ESD (Electrostatic Discharge) protection



SATEL MCCU-30


Communication technologies	LTE Cat 4 (RX MIMO)
	UHF 403 ... 473 MHz
	WiFi 802.11a/b/g/n/ac 2.4 GHz and 5 GHz
	Bluetooth V5.2
Interface	1 GB Ethernet
Operating voltage range	+9 ... +40 VDC (-15% / +20%)
Power consumption, typical	< 10 W
Built for cybersecurity, aligned with RED 3.3(d) and CRA	



SATEL SECURE REMOTE

SATEL SECURE REMOTE is a cloud-based device management system designed to enhance the value of your SATEL device by addressing maintenance requirements and simplifying configuration complexities in machine control applications.

When combined with the SATEL MCCU-30, it presents a comprehensive connectivity solution that prioritizes user-friendliness and peace of mind, providing significant value to customers.



SATEL VISIONERDS ARE HERE TO HELP YOU

We know how to make intelligent machines and work sites seamless in their connections, good for business and safe for everyone with future proof MultiTech connectivity solutions. Feel free to contact our experts; SATEL Visionerds.



SATEL MCCU-20

The SATEL MCCU-20 is a unique dual-technology RTK transceiver for receiving RTCM correction data either with UHF radio from local base station or from internet with LTE interface by using NTRIP protocol.

SATEL MCCU-20 has built-in NTRIP client and RS-232 interface, the current GNSS system capabilities can be upgraded to have always the possibility to receive RTCM corrections, no matter whether working in rural areas where

no cellular coverage is present, or receiving RTCM corrections from NTRIP caster services when operating in areas where cellular coverage is available.

SATEL MCCU-20 has IP67 and IP69K classification and it withstands vibration and shock. It is based on field proven mechanics, and all the electrical connections are equipped with surge and ESD (Electrostatic Discharge) protection.



SATEL MCCU-20

SATEL order code	YT0200 SATEL MCCU-20 EU, with encryption support, with eSIM YT0205 SATEL MCCU-20 EU, w/o encryption support, with eSIM YT0210 SATEL MCCU-20 US/CA, with encryption support, with eSIM YT0225 SATEL MCCU-20 BR, with encryption support, with eSIM
Communication modules	LTE: (NTRIP application, NMEA position upstream) UHF: 410 ... 475 / 902 ... 928 MHz radio (RTK Receiver)
Serial interface	RS-232 (TD, RD lines)
Operating voltage range	+9 ... +30 VDC (-15% / +20%)
Power consumption	Typ. 2.4 W (NTRIP receive) / Typ. <1 W (RTK receive)
Serial data speed	4800 – 460800 bps

SATEL MCCU-10 / SATEL MCCU-10C


SATEL MCCU-10 / -10C are heavy-duty receiver radio modems that meet the requirements of machine control, smart farming, and marine applications. Both are built to withstand dirt, vibration, sand, dust, liquids, and lightning. They feature robust electrical protection: the power and data lines, as well as the antenna interface, are surge protected. SATEL MCCU-10 / -10C also have additional filtering on GNSS frequencies.

SATEL MCCU-10 / -10C feature an IP67 / IP69K sealed housing that withstands high-pressure and hot-water cleaning, together with a multifrequency radio module. SATEL MCCU-10 comes with an RS-232 interface, while SATEL MCCU-10C comes with CAN and RS-232 interfaces. In addition SATEL MCCU-10C is equipped with RGB led on site of the device for status indication.





SATEL MCCU-10 / SATEL MCCU-10C

SATEL order code	YT0101 SATEL MCCU-10 YT0251 SATEL MCCU-10C
Frequency	403 ... 473 / 902 ... 928 MHz
Channel width	12.5, 20, 25 kHz @ 403 ... 473 MHz
Spreading method	Frequency hopping spread spectrum @ 902 ... 928 MHz
Sensitivity, typical	-112 dBm / -109 dBm
Interface	RS-232 (SATEL MCCU-10) CAN, RS-232 (SATEL MCCU-10C)
Data speed (max)	Serial: – 115200 bps Radio: – 28800 bps @ 403 ... 473 MHz – 115200 bps @ 902 ... 928 MHz
Operating voltage range (-15% / +20%)	+7 ... +27.5 Vdc (SATEL MCCU-10) +9 ... +30 Vdc (SATEL MCCU-10C)



To ease up the SATEL MCCU-20 configuration SATEL offers: **SATEL NARS-BT** Bluetooth device together with **SATEL Command** application (for iOS and Android).




SATEL CONNECT: GLOBAL CONNECTIVITY SOLUTION

The SATEL CONNECT is a unique cellular connectivity service concept that solves complex cellular subscription and SIM card issues.

Each SATEL MCCU device contains a SATEL CONNECT eSIM solution by default. It is perfect for machine control applications because SIM installations are not needed for the devices that can be in very hard-to-reach locations.



satel.hapyservices.com



SATEL RTK BRIDGE KIT

SATEL RTK BRIDGE KIT enhances the GNSS RTK correction signal coverage on worksites.

It is ideal solution for cost effective precise positioning on applications where harsh environments are present, such as construction, mining, agriculture and surveying.

SATEL RTK BRIDGE KIT allows you to achieve significant cost savings while getting centimeter level accuracy for each work machine operation on your worksite!


- No RTK base station needed
- Supports mixed fleets
- Tested for harsh environments
- Designed especially for off-highway vehicle installations
- High power version available for long range

Standard kit (with SATEL MCCU-20 and SATEL Proof-TR489) allows users to achieve several kilometres of coverage with standard 1W TX power.


Extended kit (with SATEL MCCU-20 and SATEL-EASy Pro+) allows users to achieve even several tens of kilometres coverage with 35W TX power.



STANDARD KIT



EXTENDED KIT



LONG DISTANCES MADE SHORT

SATEL-VHF is a half-duplex radio modem working on frequency range 135 ... 175 MHz. A special advantage of the VHF frequency band is the extremely wide coverage. With the same carrier power and antenna gain, the connection ranges are 30 to 50 per cent larger than those reached with an equivalent UHF radio modem.



SATEL-VHF

SATEL order code	YM5050 SATEL-VHF
Frequency	135 ... 175 MHz
Tuning range	40 MHz
Channel width	12.5 / 20 / 25 kHz
TX power (max.)	5 W
Interface	RS-232, -422, -485
Data speed (max.) radio / serial	19200 bps / 115200 bps

**NEW RADIO
AVAILABLE SOON**

SATEL-EASY+

SATEL-EASy+ family offers improved LCD and more memory, several interfaces are available from standard serial (SATEL-EASy+) to Ethernet / Bluetooth / USB (SATEL-EASy+ ETH). Both are with the same functionality: Data transfer, diagnostics, configuration and updating the device.

SATEL-EASy+ and SATEL-EASy+ ETH both are available on frequency range 403 ... 473 MHz that is a common frequency range in Europe and in USA, and in addition SATEL-EASy+ is available on lower frequency range 320 ... 380 MHz, that is an excellent choice for GNSS industry in Asia and utility business in the Middle East.

All interfaces are available at the same time with SATEL-EASy+ ETH. For example ETH for system data, USB for NMS monitoring and Bluetooth for field configuration. Bluetooth interface is available also for system data; for example the radio to be connected to a GNSS receiver.

SATEL EASy+ ETH is optimized for Modbus communication protocols, sending only the protocol payload through the radio channel for maximum efficiency. SATEL-EASy+ ETH is with Modbus conversion feature. Multiple networking modes are supported:

- TCP Server / TCP Client
- UDP/IP data transfer
- ICMP response (local)
- Dual IP port structure:
 - Data Port for system data communication
 - Diagnostics Port for remote management system

ETHERNET

- 10/100 Mbps, Ipv4
- TCP/UDP connectivity
- DHCP Client -support
- Optimized for Modbus communication protocols
- Supports SCADA systems and PLC communication


BLUETOOTH V4.2

- Server and client modes (SPP & BLE)
- System data transfer, configuration or NMS diagnostics
- SATEL Command mobile app for local configuration

USB 2.0 DEVICE MODE

- For system data or NMS diagnostics
- Appears as a virtual COM port when connected to a device





SATEL-EASy+ radios are compatible with e.g. SATELLINE-EASy and -TR4+ based radios as well as with SATELLINE-3AS NMS modems.

To ease up the SATEL-EASy+ ETH configuration, SATEL offers SATEL Command application (for iOS and Android).



SATEL-EASy+ D15 connector



**SATEL-EASy+ ETH
M8-power, M8-USB, M8-ETH connectors**

SATEL-EASY+	
SATEL order code	320 ... 380 MHz: YM6030 SATEL-EASy+ (with AES) YM6035 SATEL-EASy+ YM6060 SATEL-EASy+ (with display and AES) YM6065 SATEL-EASy+ (with display)
	403 ... 473 MHz: YM6010 SATEL-EASy+ (with AES) YM6015 SATEL-EASy+ YM6050 SATEL-EASy+ (with display and AES) YM6055 SATEL-EASy+ (with display) YM6070 SATEL-EASy+ ETH (with display and AES)
Frequency	320 ... 380 / 403 ... 473 MHz (SATEL-EASy+) 403 ... 473 MHz (SATEL-EASy+ ETH)
Tuning range	60 (320 ... 380 MHz) / 70 MHz (403 ... 473 MHz)
Channel width	6.25 / 12.5 / 20 / 25 kHz @ 320 ... 380 MHz 12.5 / 20 / 25 kHz @ 403 ... 473 MHz
RX sensitivity	-115 dBm @ 12.5 kHz (4FSK) / -113 dBm @ 25 kHz (4FSK) -102 dBm @ 25 kHz (16FSK)
TX power (max.)	1W
Interface	RS-232, -422, -485 (SATEL-EASy+) USB, ETH, Bluetooth (SATEL-EASy+ ETH)
Operating voltage range	+7 ... +27.5 Vdc (-15 % / +20 %)
Power consumption TX / RX	< 5.5 W / < 1.5 W
Data speed (max.)	Radio 28800 bps Serial 115200 bps (SATEL-EASy+) Ethernet 10/100 Mbps, USB2.0 (SATEL-EASy+ ETH)

NMS

NMS (Network Management System) protocol compatibility (with routing, diagnostics and packet filters) offers the following benefits:

- Enhanced reliability, through advance indication of anticipated faults and failures
- Reduced configuration and maintenance costs, through remote configuration
- An efficient tool for network development

THE FOLLOWING VARIANT IS COMING NEXT

Multifrequency transceiver:

- Licensed 403 ... 473 MHz
- License-free 869.400 ... 869.650 MHz (ask availability for other freq. on 856 ... 876 MHz range)
- License-free 902 ... 928 MHz

SOLUTIONS FOR THE TOUGHEST PLACES


SATEL-EASy Pro+ is a new IP67 classified UHF radio modem with a high 35 W power transmitter, wide 70 MHz tuning range (403 ... 473 MHz) in one hardware and selectable channel spacing.

SATEL-EASy Pro+ is equipped with one antenna port and either with one RS-232 port for data (with NMS features, no diagnostic port) or with dual serial port, RS-232 by default and RS-485/-422 data ports optional (with NMS features and diagnostic port). Note! Dual serial port model is needed for NMS master operation. Supported AES128 (by default) / AES256 (as an order option) encryption on radio channel increases the data security. Future options include for example lower frequency band 320...380 MHz.

Due to the high transmitting power, connection distances more than 80 kilometres can be covered in favorable conditions.

SATEL-EASy Pro+

SATEL order code	Models with one serial port: YM6820 SATEL-EASy Pro+ (with AES, 25 W, for EU) YM6823 SATEL-EASy Pro+ (with AES, 35 W) YM6825 SATEL-EASy Pro+ (w/o AES, 25 W, for EU) YM6830 SATEL-EASy Pro+ (with AES, 25 W, for AU) YM6833 SATEL-EASy Pro+ (w/o AES, 35 W) YM6835 SATEL-EASy Pro+ (w/o AES, 25 W, for AU) YM6840 SATEL-EASy Pro+ (with AES, 35 W, for BR) YM6845 SATEL-EASy Pro+ (w/o AES, 35 W, for BR)
	Models with dual serial port: YM6843 SATEL-EASy Pro+ (with AES, 35 W) YM6853 SATEL-EASy Pro+ (w/o AES, 35 W) YM6860 SATEL-EASy Pro+ (with AES, 25 W, for EU) YM6865 SATEL-EASy Pro+ (w/o AES, 25 W, for EU) YM6870 SATEL-EASy Pro+ (with AES, 25 W, for AU) YM6875 SATEL-EASy Pro+ (w/o AES, 25 W, for AU)
Frequency	403 ... 473 MHz
Tuning range	70 MHz
Channel width	12.5 / 20 / 25 kHz
RX sensitivity	-114 dBm
TX power (max.)	35 W (Limited 25 W version is available as an order option)
Interface	RS-232 / HW model with data port 2: RS-232/-485/-422 (data/NMS)
Operating voltage range	+9 ... +30 Vdc (-15% / +20%)
Power consumption	TX: 9 ... 10 W @ 1W output power TX: 60 ... 72 W @ 25 W output power TX: 84 ... 97 W @ 35 W output power RX: 1.8 ... 2.3 W Sleep mode: 0.9 ... 1.4 W
Data speed (max.) radio / serial	28800 bps / 115200 bps



SATEL Proof radios are heavy-duty models. Housing of these models has the IP69K rating, which is the highest protection available. It protects against ingress of dust, high temperature and high-pressure water.

HEAVY-DUTY SOLUTION FOR HARSH ENVIRONMENT

SATEL Proof radio with IP67 / IP69K-classifications meets, for example, the requirements of machine control, smart farming and marine applications. It is a flexible and cost-effective solution that has profound electrical protection; both the power and data lines as well as the antenna interface are surge protected. It also has additional filtering on GNSS frequencies.

SATEL Proof-TR4+ / -TR9

SATEL order code	YM6577 SATEL Proof-TR4+ (with AES) YM6578 SATEL Proof-TR4+ YM6410 SATEL Proof-TR9 YM6411 SATEL Proof-TR9 for US, CA YM6412 SATEL Proof-TR9 for AU, NZ, BR YM6420 SATEL Proof-TR4+ OA YM6597 SATEL Proof-R4+ (RX only with AES) YM6596 SATEL Proof-R4+ (RX only)
Frequency	403 ... 473 / 902 ... 928 MHz
Channel width	12.5 / 20 / 25 kHz @ TR4+
Spreading method	Frequency hopping @ TR9
RX sensitivity	-118 ... -105 dBm
TX power (max.)	1 W
Interface	RS-232 (TD, RD lines)
Operating voltage range	+7 ... +27.5 Vdc (-15% / +20%)
Power consumption TX / RX	7 / 1.2 W (typical)
Data speed (max.) radio / serial	28800 bps / 115200 bps @ TR4+ 115200 bps / 115200 bps @ TR9



SATEL Proof-TR4+ / -TR9
SATEL Proof-TR489

To ease up the SATEL Proof radios configuration SATEL offers: SATEL NARS-BT Bluetooth device together with SATEL Command application (for iOS and Android).

SATEL Proof-TR489

SATEL order code	YM6920 SATEL Proof-TR489 (with AES, region all), YM6925 SATEL Proof-TR489 (w/o AES, region all) YM6930 SATEL Proof-TR489 (with AES, for US/CA 400/915), YM6935 SATEL Proof-TR489 (w/o AES, for US/CA 400/915) YM6940 SATEL Proof-TR489 (with AES, for AU/BR 400/915), YM6945 SATEL Proof-TR489 (w/o AES, for AU/BR 400/915) YM6950 SATEL Proof-TR489 (with AES, for EU 400/869), YM6955 SATEL Proof-TR489 (w/o AES, for EU 400/869)
Frequency	403 ... 473 / 869.4 ... 869.65 / 902 ... 928
Tuning range	70 MHz / 0.25 MHz / frequency hopping spread spectrum
Channel width	12.5, 20, 25 kHz / 25, 50 kHz / 7 user selectable hopping bands
RX sensitivity	-113 dBm / -108 dBm / -106 dBm
TX power (max.)	1 W / 0.5 W / 1 W
Interface	RS-232 (TD, RD lines)
Operating voltage range	+7 ... +27.5 Vdc (-15% / +20%)
Power consumption TX / RX	7 / 1.3 W (typical)
Data speed (max.) radio / serial	28800 bps / 115200 bps @ 400 MHz 38400 bps / 115200 bps @ 869 MHz 115200 bps @ 915 MHz

COMPACT AND COMPATIBLE

SATEL has a wide range of OEM radio modules for system manufacturers to integrate into customer solutions. They are secure, customizable and flexible in mounting options. SATEL's solutions are widely compatible and also support other manufacturers' radio protocols.

The latest addition to SATEL radio modules is the SATEL GO radio module family. SATEL GO modules introduce new revolutionary features: one to three frequencies in the same small module and more practical interfaces. The design is compact and the integration easy.

SATELGO

SATEL-TR49 SnapOn

SATEL-TR49 SnapOn fits to a standard PCIe bus. This makes it compatible with millions of equipment already in the market, and the integration is easy. If there is Mini PCIe bus, it can replace other technologies such as cellular and LoRa. Ideal for real-time IoT applications!


- Ultra-compact design
- Easy integration and deployment
- Possibility of power over USB (max 500 mW, more with extra input)
- Robust mounting and interfaces



SATEL order code	YM8600 region all, with AES YM8605 region all, w/o AES YM8610 region US/CA, with AES YM8615 region US/CA, w/o AES YM8630 region AU/BR, with AES YM8635 region AU/BR, w/o AES
Frequency	410 ... 475 / 902 ... 928 MHz
Channel width	12.5 / 25 kHz @ 400 MHz
Spreading method	Frequency hopping @ 900 MHz
RX sensitivity	-120 dBm @ 400 MHz -109 dBm @ 900 MHz
TX power (max.)	1 W
Interface	CMOS / UART
Operating voltage	+3.3 Vdc +/-9%
Power consumption TX / RX	4.5 – 4.8 W / 400 mW @ 400 MHz 4.0 W / 400 mW @ 900 MHz
Data speed (max.) radio / serial	19200 bps (115200 bps @ 900 MHz) / 115200 bps

SATEL-TR49

SATEL order code	YM8490 region all, with AES YM8495 region all, w/o AES YM8500 region US/CA, with AES YM8505 region US/CA, w/o AES YM8510 region AU/BR, with AES YM8515 region AU/BR, w/o AES
Frequency	410 ... 475 / 902 ... 928 MHz
Channel width	12.5 / 20 / 25 kHz @ 400 MHz
Spreading method	Frequency hopping @ 900 MHz
RX sensitivity	-120 dBm @ 400 MHz -109 dBm @ 900 MHz
TX power (max.)	1 W
Interface	CMOS / UART
Operating voltage range	+3.7 ... +5.5 Vdc
Power consumption TX / RX	4.8 W (TX 1 W) / 440 mW (RX) @ 400 MHz 4.1 W (TX 1 W) / 440 mW (RX) @ 900 MHz
Data speed (max.) radio / serial	19200 bps (115200 bps @ 900 MHz) / 115200 bps



Ask availability from SATEL for the modules with region limitations.

SATEL-R4+

SATEL order code	YM7490 with AES YM7495 w/o AES YM7491 DTE connector at TOP YM7496 w/o AES, DTE connector on TOP
Frequency	403 ... 473 MHz
Tuning range	70 MHz
Channel width	12.5 / 20 / 25 kHz programmable
RX sensitivity	-115 dBm
Interface	CMOS-UART
Operating voltage range	+3.8 ... +5.5 Vdc
Power consumption RX	0.86 W
Data speed (max.) radio / serial	28800 bps / 115200 bps



SATEL-R4+

RECEIVER ONLY

SATEL-TR4+

SATEL order code	YM7470 with AES YM7475 w/o AES YM7480 DTE connector at TOP YM7485 w/o AES, DTE connector at TOP YM7440 OA
Frequency	403 ... 473 MHz
Tuning range	70 MHz
Channel width	12.5 / 20 / 25 kHz programmable
RX sensitivity / TX power (max)	-115 dBm / 1 W
Interface	CMOS-UART
Operating voltage range	+3.8 ... +5.5 Vdc
Power consumption TX / RX	4.8 W / 0.89 W
Data speed (max.) radio / serial	28800 bps / 115200 bps



SATEL-TR4+

TRANSCEIVER


SATEL-TR489

SATEL order code	YM8810 region all YM8815 w/o AES, region all YM8816 w/o AES, region all, DTE connector at TOP YM8820 region US/CA YM8825 w/o AES, region US/ CA YM8830 regio AU/BR 400/915 YM8835 w/o AES, region AU/BR 400/915 YM8850 region EU 400/869 YM8855 w/o AES, region EU 400/869 YM8860 region EU 869 YM8865 w/o AES, region EU 869
Frequency	403 ... 473 MHz / 869.4...869.65 MHz (856...876 MHz*) / 902 ... 928 MHz
Tuning range	70 MHz / 20 MHz / frequency hopping spread spectrum
Channel width	12.5, 20, 25 , 50*) kHz / 25, 50 kHz / 7 user selectable hopping bands
RX sensitivity / TX power (max.)	-115 dBm / -110 dBm / -108 dBm 1 W / 0.5 W / 1 W
Interface	CMOS-UART
Operating voltage range	+3.8 ... +5.5 Vdc
Power consumption TX / RX	4.7 W / 0.73 W
Data speed (max.) radio / serial	28800 bps / 115200 bps @ 400 MHz 38400 bps / 115200 bps @ 800 MHz 115200 bps / 115200 bps @ 900 MHz

*) Ask availability from SATEL.


SATEL-TR300

SATEL order code	YM7300 with AES YM7305 w/o AES YM7315 w/o AES, DTE connector on TOP Japan variants, please contact SATEL
Frequency	320 ... 380 MHz
Tuning range	60 MHz
Channel width	6.25 / 12.5 / 20 / 25 kHz programmable
RX sensitivity / TX power (max.)	-113 dBm / 1 W
Interface	CMOS-UART
Operating voltage range	+3.8 ... +5.5 Vdc
Data speed (max.) radio / serial	28800 bps / 115200 bps
Power consumption TX / RX	6.4 W / 0.9 W



SATEL-TR489

LICENCE FREE



SATEL-TR300



LICENCED

SATELLINE-M3-TR9

SATEL order code	YM7900 region all YM7920 DTE TOP/U.FL same side YM7910 region US/CA YM7915 region AU
Frequency	902 ... 928 MHz
Spreading method	Frequency hopping
RX sensitivity / TX power (max.)	-109 dBm / 1 W
Interface	CMOS-UART
Operating voltage range	+3.5 ... +5.5 Vdc
Power consumption TX / RX	3.2 W / 0.3 W
Data speed (max.) radio / serial	115200 bps

SATELLINE-M3-R9

SATEL order code	YM7950
Frequency	902 ... 928 MHz
Spreading method	Frequency hopping
RX sensitivity	-109 dBm
Interface	CMOS-UART
Operating voltage range	+3.5 ... +5.5 Vdc
Power consumption TX / RX	0.3 W
Data speed (max.) radio / serial	115200 bps

**SATELLINE-M3-TR9****FREQUENCY HOPPING
TRANSCEIVER MODULE****SATELLINE-M3-R9****FREQUENCY HOPPING
RECEIVER MODULE**

SOLUTIONS FOR TOUGHEST ENVIRONMENT



SATEL-B2 motherboard and SATEL radio module combinations are available either as enclosed assemblies or as a board level OEM variant.

SATEL-B2 motherboard is easy to integrate into the host device and due to the modular structure, user can select the optimum radio solution fitting to their application.

Three variants of SATEL-B2 motherboard are available as a board level OEM variant:

- MP1 = With horizontal female 26-pin connector
- MP2 = With horizontal 26-pin female connector with D15 female adapter
- MP3 = With vertical 26-pin male connector

Radio module for each motherboard variant as defined by the order code. And the following RF adapters are available separately: u.FL to TNCf / SMAf / MMCxf / MCXf / BNCf.

For example, the variants with SATEL-TR489 module, please visit:

<https://www.satel.com/products/radio-modems/satel-tr489/>



The combination of SATEL-B2 motherboard and radio module is available as enclosed assembly inside an aluminium enclosure with D15 female data connector and mounting ears. Three models available:

- ME1 = With TNC female antenna connector
- ME2 = With TNC female antenna connector and DIN clip
- ME3 = With BNC female antenna connector and DIN clip

To see all available variants inside an aluminium enclosure and product codes for those, please visit:

<https://www.satel.com/products/radio-modems/satel-b2-motherboard-with-enclosure/>



MP2 with TNC female RF adapter



ME1 TNC female antenna connector

THE WORLD IS OPEN



BLUETOOTH DEVICES

SATEL BT-RS232 is an IP66-rated robust and waterproof Bluetooth to RS-232 serial port adapter. It offers a compact and easily integrable solution for devices that needs to communicate without a cable connection.

SATEL BT-RS232 is equipped with long range Bluetooth 2.1, that offers connection distances upto 400 meters.

SATEL BT-RS232

SATEL order code	YI0232 SATEL BT-RS232 adapter
Electrical interface	RS232
Data speed serial	115200 bps
TX power	+12 dBm with Bluetooth BR/EDR
RX sensitivity	-96 dBm
Operation mode	Slave mode
Operating voltage	+9 ... +27.5 Vdc (-15% / +20%)



SATEL BT-RS232

SATEL I-LINK 100 is an I/O-converter, intended to be use together with SATEL radio data modems, facilitating transparent transfer of contact information or analog signals from one location to another.

With the I-LINK 100 converter and SATEL radio modem you can transfer information on a switch position or the reading of a measuring gauge (analog or digital) from the point of surveillance to the control station and vice versa.

The I-LINK 100 can be used in Point-to-Point or in Point-to-Multipoint mode, for transferring information between a master station and several remote stations. In order to offer even more flexibility, a Modbus compatible version is available too.

The SATEL NARS-BT is a robust Bluetooth – RS232 device. Together with SATEL COMMAND mobile application, they solve wireless configuration needs in the field.

- Quick and easy to perform daily setting changes from single channel setting to more complex full settings list
- Different settings and several use cases can be covered, and no time is wasted for hard-to-find settings or too complex technical terms
- SL command based configuration operations, supported by wide range of SATEL devices
- Quick mode change between radio interfaces (LTE/UHF) when using with SATEL MCCU-20

SATEL NARS-BT


SATEL order code	YI0220
Electrical interface and speed	RS232, 115200 bps
Radio interface	Bluetooth v4.2 BR/EDR and BLE compliant (Operation mode: Slave)
Operating voltage	+9 ... +30 VDC (-15% / +20%)



SATEL NARS-BT

SATEL I-LINK 100 has 4 digital I/O ports with built-in relays and 2 analog I/O ports.

- SATEL I-LINK 100 (YI0007)
- SATEL I-LINK 100 Modbus compatible version (YI0017)



SATEL I-LINK 100

Software — Ready, steady, go!

SOFTWARE

SATEL software

	SATEL NETCO DEVICE	SATEL NETCO DESIGN	SATEL Configuration Manager	SATELLINE SaTerm	SATEL NETCO NMS	SATEL NMS PC
SATEL MCCU-10				*		
SATEL MCCU-20				*		
SATEL-EASy+ (RS232/422/485)				*		
SATEL-EASy+ ETH (ETH/BT/USB)				*		
SATEL-EASy Pro+						
SATEL Proof-TR4+, -R4+				*		
SATEL Proof-TR489				*		
SATEL Proof-TR9				*		
SATELLINE-3AS VHF						
SATEL-TR4+, -R4+				*		
SATEL-TR300				*		
SATEL-TR49				*		
SATEL-TR489				*		
SATEL-TR49 SnapOn				*		
SATELLINE-M3-TR9, -R9				*		
SATEL-TR4+ OA				*		
SATEL-B2-TR4+				*		
SATEL-B2-TR489				*		
SATEL-B2-TR4+ OA				*		

*) SL command support

SATEL NETCO DEVICE

SATEL NETCO DEVICE is a software for configuring and updating a device. The configuration parameters can be read and written from/to the locally connected, powered device. The device configuration can be also created/saved/explored from/to a file without device connection.

The most common use case for which the SATEL NETCO DEVICE is optimized for is editing existing parameters in a SATEL radio product using local connection, such as serial interface.

SATEL NETCO DESIGN

SATEL NETCO DESIGN is an intuitive and user-friendly network configuration software for network design and management. The software supports configuration of the Routing Setup and NMS Routing Setup modes for SATEL-EASy+ product family.

The user interface of the product is browser-based and can therefore be used both locally and remotely. Design with graphical user interface for easy optimizing network design and deployment in a few simple steps, with local and remote connection to SATEL radios. SATEL NETCO DESIGN supports importing also .saxd file format, files created with the SATEL NMS PC software.

SATEL NETCO NMS

SATEL NETCO NMS is an intuitive and user-friendly network configuration software for network design and management with radio network monitoring option. The software supports configuration of the Routing Setup and NMS Routing Setup modes for SATEL-EASy+ product family.

The user interface of the product is browser-based and can therefore be used both locally and remotely. Design with graphical user interface for easy optimizing network design and deployment in a few simple steps, with local and remote connection to SATEL radios. SATEL NETCO NMS supports importing also .saxd file format, files created with the SATEL NMS PC software.

SATELLINE SaTerm

SATELLINE SaTerm is a terminal software for configuring the Routing Setup mode and for configuring and testing the radios. Routing Setup refers to Message Routing feature for SATEL-EASy+ and SATELLINE-EASy family radio modems, where messages can be automatically routed over the radio network to correct recipient terminal. This SW can assist in tests procedures and configuration for the radios via terminal interface with SL command support.

SATEL NMS PC

SATEL NMS PC is a software for creating and managing SATEL-EASy+ and SATELLINE-3AS VHF product families for NMS Routing networks with radio network monitoring option. NMS Routing refers to NMS Message Routing feature, where messages can be automatically routed over the radio network to correct recipient terminal, monitoring and diagnostics included for the radio network. Graphical design of topology for NMS Message Routing, remote modification of settings, online storing and trending of field data with programmable alarm triggers.

SATEL Configuration Manager

SATEL Configuration Manager is a software for SATEL radio device configuration and reprogramming. The parameters can be read and written from/to the connected, powered device. The program file can be saved into a separate file to be used to other devices.

The most common use case for which the SATEL Configuration Manager is optimized for is editing existing parameters in a SATEL radio product using locally connected product over a serial interface.

PROTOCOLS

SATEL radio modems are compatible with all commonly used industrial protocols. Here are some examples of the protocols: ANSI, CACTUS, COMLI, DNP 3.0, Exoline, HostLink, IEC 60870-5-101, Mewtocol, Modbus ASCII, Modbus RTU, Modbus TCP, Modbus RTU over TCP, Profibus DP, R-com, RP-570, RP-571, SATELLINK, S-bus, Siemens 3946 (R), Siemens Sinaut ST1/ST7 FT1.2/FT2.0, Siemens Sinaut ST7 FT2.0 and NMEA 0183, Ethernet/IP, SATEL NMS, Rockwell DT1 etc.

Ask for more information from your local distributor.

Antennas & cables

Antennas

- Half Wave Antennas for frequencies 400 ... 470 MHz for short distances.
- Quarter Wave Antennas for frequencies 400 ... 470 MHz and 869 MHz for short distances.
- Helix Antennas for frequencies 400 ... 470 MHz for short distances.
- Directional Antennas for frequencies 330 ... 470 MHz, 869 MHz and 135 ... 174 MHz for long distances.
- Omnidirectional Antennas for frequencies 330 ... 470 MHz, 869 MHz and 135 ... 174 MHz for long distances.



Cables

- CRF-1 RG58 length 1 meter with TNC male / TNC female -connectors.
- CRF-5F RG58 length 5 meter with TNC male / TNC female -connectors or CRF-5M TNC male / TNC male -connectors.
- ECOFLEX10 low loss (0.9 dB / 10 m) cable for cable lengths up to 20 meter with N or TNC -connectors.
- ECOFLEX15 low loss (0.6 dB / 10 m) cable for cable lengths over 20 meter with N -connectors.

We can also offer a wide range of interface and power cables, for example:




- Connecting data/power cables with D9 male/female mating connectors, direct and crossover cables.
- CRS-PB length 2 meter, includes power supply wires, with D15 / D9 male -connectors for RS-485 interface.
- CRS-35W 8-pin 2 m cable ODU 8-pin male / D9 female.
- C-P-Pro+ 2m Power cable 2 m, ODU 2-pin male / 4 mm lab plugs.

Please contact your local distributor to get more information regarding cable types.

1) Check product details	SATEL MCCU-20	SATEL MCCU-30	SATEL-EASy+	SATEL-EASy Pro+	SATEL-B2	SATEL-TR4+ / -R4+	SATEL-TR489	SATEL-TR49	SATEL-TR300	SATEL-TR49 SnapOn	SATEL Proof-TR4+, -TR9	SATEL Proof-TR489	SATELLINE-M3-TR9 / -R9	SATEL I-LINK
Frequency range														
UHF	.	.	.	.		.			.					
VHF														
UHF & Licence free					1)		.	.		.	.	.	.	
LTE	.	.												
Bluetooth		.												
WiFi		.												
Interfaces														
RS-232	.		.	.	.						.	.		.
RS-422			.	.										
RS-485			.	.										
CMOS-UART						.	.	.	.	.			.	
Ethernet		.	1)											
USB			1)											
Digital / Analog I/O														.
Bluetooth			1)											
Tuning range														
≤ 2 MHz					1)		.					.		
20 MHz							.							
65 MHz	.							.	1)	.				
60 / 70 MHz	1)	.	.	.	1)	.	.				.	.		
FHSS	.				1)		.	.		.	.	.	.	
Channel width kHz														
Fixed (12.5 or 20 or 25)														
Programmable (6.25 / 12.5 / 20 / 25)			1)						.					
Programmable (12.5 / 20 / 25)	.	.		.		.		.			.			
Programmable (12.5 / 25)									1)	.				
Programmable (12.5 / 20 / 25 / 50)					1)		.					.		
FHSS	.				1)		.	.			.		.	
Max. TX power														
500 mW					1)		.							
1 W	.	.	.		1)	1)	.	.	.	.	.	1)	1)	
5 W														
35 W				.										
Operating voltage range														
+3.3 Vdc +/- 9%										.				
+3.5 ... +5.5 Vdc													.	
+3.7 ... +5.5 Vdc								.						
+3.8 ... +5.5 Vdc						.	.		.					
+7 ... +25 Vdc (-15% / +20%)														
+7 ... +27.5 Vdc (-15% / +20%)			.		.						.	.		
+9 ... +30 Vdc (-15% / +20%)	.	.		.										
+10.6 ... +25 Vdc (-15% / +20%)														
Housing														
Aluminium IP44			.											
Aluminium IP67	.	.		.							.	.		
Aluminium IP69K	.	.									.	.		
Sheet metal aluminium / Stainless steel					1)									.
Module: PCB card only					1)	.	.	.	.	.			.	
Interface connector														
RJ-45			1)											
D9														
D15			1)		1)									.
ODU 8 pin				.										
26 pin header / 26 pin strip														

1) Check product details	SATEL MCCU-20	SATEL MCCU-30	SATEL-EASy+	SATEL-EASy Pro+	SATEL-B2	SATEL-TR4+ / -R4+	SATEL-TR489	SATEL-TR49	SATEL-TR300	SATEL-TR49 SnapOn	SATEL Proof-TR4+, -TR9	SATEL Proof-TR489	SATELLINE-M3-TR9 / -R9	SATEL I-LINK
Frequency range														
UHF	•	•	•	•		•			•					
VHF														
UHF & Licence free					1)		•	•		•	•	•	•	
LTE	•	•												
Bluetooth		•												
WiFi		•												
Interfaces														
RS-232	•		•	•	•						•	•		•
RS-422			•	•										
RS-485			•	•										
CMOS-UART						•	•	•	•	•			•	
Ethernet		•	1)											
USB			1)											
Digital / Analog I/O														•
Bluetooth			1)											
Tuning range														
≤ 2 MHz					1)		•					•		
20 MHz							•							
65 MHz	•							•	1)	•				
60 / 70 MHz	1)	•	•	•	1)	•	•				•	•		
FHSS	•				1)		•	•		•	•	•	•	
Channel width kHz														
Fixed (12.5 or 20 or 25)														
Programmable (6.25 / 12.5 / 20 / 25)			1)						•					
Programmable (12.5 / 20 / 25)	•	•		•		•		•			•			
Programmable (12.5 / 25)									1)	•				
Programmable (12.5 / 20 / 25 / 50)					1)		•					•		
FHSS	•				1)		•	•			•		•	
Max. TX power														
500 mW					1)		•							
1 W	•	•	•		1)	1)	•	•	•	•	•	1)	1)	
5 W														
35 W				•										
Operating voltage range														
+3.3 Vdc +/- 9%										•				
+3.5 ... +5.5 Vdc													•	
+3.7 ... +5.5 Vdc								•						
+3.8 ... +5.5 Vdc						•	•		•					
+7 ... +25 Vdc (-15% / +20%)														
+7 ... +27.5 Vdc (-15% / +20%)			•		•						•	•		
+9 ... +30 Vdc (-15% / +20%)	•	•		•										
+10.6 ... +25 Vdc (-15% / +20%)														
Housing														
Aluminium IP44			•											
Aluminium IP67	•	•		•							•	•		
Aluminium IP69K	•	•									•	•		
Sheet metal aluminium / Stainless steel					1)									•
Module: PCB card only					1)	•	•	•	•	•			•	
Interface connector														
RJ-45			1)											
D9														
D15			1)		1)									•
ODU 8 pin				•										
26 pin header / 26 pin strip					1)									
USB			1)							•				
1.27 mm pitch socket						•	•	•	•				•	
Deutsch DT04-6P-CL09	•										•	•		
Screw connector														•
Model or variant w. display			•	•										

Available frequencies for SATEL radio modems



Size / Weight			
174 x 95 x 46 mm / < 500 g	SATEL Proof-TR4+/-TR9 / -TR489	138 x 67 x 29 mm / < 350 g	SATEL-EASy+
174 x 95 x 47 mm / 520 g	SATEL MCCU-20	126 x 63 x 23 mm / < 300 g	SATEL-B2 with enclosure
182 x 187 x 55 / 1550 g	SATEL MCCU-30	57 x 36 x 6.9 mm / 20 g	SATEL-TR4+, SATEL-TR49, SATEL-TR489, SATEL-R4+, SATEL-TR300
180 x 138 x 71mm / 1400 g	SATEL-EASy Pro+	57 x 36 x 6.7 mm / 20 g	SATELLINE-M3-TR9, SATELLINE-M3-R9
139 x 67 x 29 mm / < 300 g	SATELLINE-3AS VHF	51 x 30 x 4.75 mm / 10 g	SATEL-TR49 SnapOn

IMPORTANT

SATEL PRODUCTS HAVE NOT BEEN DESIGNED, INTENDED NOR INSPECTED TO BE USED IN ANY LIFE SUPPORT RELATED DEVICE OR SYSTEM AND ARE GRANTED NO FUNCTIONAL WARRANTY IF THEY ARE USED IN ANY OF THESE APPLICATIONS.

Distributors

ALBANIA

See Croatia

AUSTRALIA

ROJONE PTY LIMITED

+61 2 9829 1555

warren@rojone.com.au

www.rojone.com.au

Rojone is serving Australia and New Zealand

AUSTRIA

See Germany

BELGIUM

See The Netherlands

BOSNIA AND HERZEGOVINA

See Croatia

BRAZIL

SATELRADIO COMUNICAÇÃO

+55 11 3090 4094

engenharia@satelradio.com.br

www.satelradio.com.br

TECHTON RADIO MODEM

+55 15 99106 3505

jaimilton@tehtonradiomodem.com.br

www.tehtonradiomodem.com.br

BULGARIA

See Greece

CAMBODIA

See South East Asia

CANADA

MDA CONTROLS INC.

+1 905 845 3666

orit.altman@mdacontrols.com

www.mdacontrols.com

METACON CANADA INC.

+1 888 563 9333

intel@metaconx.ca

www.metaconx.ca

CHILE

METCOM LIMITADA

+56 2 2335 3812

gailrybertt@metcomchile.cl

www.metcomchile.cl

CHINA P.R.

SATEL CHINA CO., LTD

+86 20 8251 4925

info@satel.cn

www.satel.cn

CROATIA

ADRINET D.O.O.

+385 1 8886 884

adrinet@adrinet.hr

www.adrinet.hr

Adrinet is serving Croatia, Albania, Macedonia, Serbia and Bosnia and Herzegovina.

CZECH REPUBLIC

CONTROLTECH S.R.O.

+420 321 7420 11

info@controltech.cz

www.controltech.eu

ControlTech s.r.o. is serving Czech Republic and Slovak Republic

DENMARK

NORTHCOM

+45 49 139 693

salg@northcom.dk

www.northcom.dk

ESTONIA

ALARMTEC AS

+372 6 511 500

alarmtec@alarmtec.ee

www.alarmtec.ee

Alarmtec AS is serving Estonia, Latvia and Lithuania.

FRANCE

COMATIS

satel@comatis.com

www.comatis.com

GERMANY

WELOTEC GMBH

+49 2554 9130 00

info@welotec.com

www.welotec.com/radio-modems

Welotec is serving Germany and Austria

GREECE

INTELLIGENT CONTROL SYSTEMS SA

+30 210 6466 276

info@controlsystem.com.gr

www.controlsystem.com.gr

HUNGARY

CONTROLTECH S.R.O.

+36 23 445 900

info@ctech.hu

www.ctech.hu/hu

ICELAND

NAUST MARINE HF

+354 414 8080

naust@naust.is

www.naust.is

INDIA

LOTUS WIRELESS

+91 891 276 1678

info@lotuswireless.com

www.lotuswireless.com

INDONESIA

PT. INZAN PERMATA

+62 21 875 2727

info@inzanpermata.id

www.inzanpermata.id

IRELAND

SIGMA WIRELESS COMMUNICATIONS LTD

+353 1 814 2100

pkinna@sigma.ie

www.sigmapwireless.com

Sigma Wireless Communications Ltd is serving Ireland and Northern Ireland.

ISRAEL

ARROWMID GROUP LTD

+972 36 247 080

info@arrowmid.com

www.arrowmid.com

ITALY

SARTELCO SISTEMI S.R.L.

+39 039 629 051

sistemi@sartelco.it

www.sartelco.com

KAZAKHSTAN

AUTOMATION AND TECHNOLOGIES LLP

+7 727 277 4949

info@automation-trade.com

www.automation-trade.com

KOREA

THOMAS CO., LTD

+82 31 467 8554

system@thomas.co.kr

www.thomas.co.kr

LATIN AMERICA-CARIBBEAN

SOLARES FLORIDA CORP

Tel +1-305-592 0593

isolares@solaresflorida.com

www.solaresflorida.com

Solares Florida is serving part of the Latin America and Caribbean countries.

LAOS

See South East Asia

LATVIA, LITHUANIA

See Estonia

LUXEMBOURG

See The Netherlands

MACEDONIA

See Croatia


MALAYSIA

DIGISELECT (M) SDN BHD

+6 03 5614 3167

enquiry@dgselect.com

www.dgselect.com



Distributors

MEXICO
ROSSBACH DE MÉXICO, S.A. DE C.V.
 +52 55 8030 3574
 contacto@rossbach.com.mx
<https://www.rossbach.com.mx>

MIDDLE EAST
EASY WORLD AUTOMATION LLC
 +971 4 447 1137
 sales@eworldme.com
www.eworldme.com/partners/satel

SAUDI TELECOMMUNICATION
 +966 13 820 0477
 mansour@stpest.com
www.stpest.com
 Saudi Telecommunication & Power
 is serving Saudi Arabia, Kuwait, UAE,
 Bahrain, Qatar and Oman.

MONTENEGRO
 See Slovenia

THE NETHERLANDS
SATEL BENELUX B.V.
 +31 255 820 009
 info@satelbv.nl
www.satelbv.nl
 SATEL Benelux is serving The Netherlands,
 Belgium and Luxembourg

NEW ZEALAND
 See Australia

NORTHERN AFRICA
 See France

NORWAY
SATEL NORGE AS
 +47 69 27 70 40
 produktinfo@satel.no
www.satel.no

PERU
MOR REPRESENTACIONES SAC
 +51 1 222 6185
 jmalmeida@morsac.com
www.morsac.com

PHILIPPINES
 See South East Asia

POLAND
ASTOR MISSION CRITICAL SP. Z O.O.
 +48 60 178 3744
 info@missioncritical.com.pl
www.missioncritical.com.pl/en

PORTUGAL
 See Spain

SERBIA
 See Slovenia

SINGAPORE
NOR OFFSHORE RENTAL PTE LTD
 +65 9159 1000
 sales.apac@offshorerental.com
<http://norgroup.com>

SLOVAK REPUBLIK
 See Czech Republic

SLOVENIA
METRONIK D.O.O
 +386 1 514 0800
 info@metronik.si
www.metronik.si

*METRONIK d.o.o is serving Slovenia,
 Serbia and Montenegro*

SOUTH AFRICA
CSTREAM
 +27 12 664 4515
 info-cs@cstream.co.za
www.cstream.co.za
 cStream serves Africa,
 excluding Northern Africa

SOUTH EAST ASIA
SATEL OY IN S.E.A.
 +66 899 276 966
 janne.kankaanpaa@satel.com
www.satel.com
 SATEL Sales Manager Mr. Janne
 Kankaanpaa serves S.E.A. region
 (Philippines, Thailand, Cambodia,
 Laos, plus other S.E.A. countries).

SPAIN
SATEL IBERIA
 +34 91 636 22 81
 info@satel-iberia.com
www.satel-iberia.com
 SATEL IBERIA is serving Spain and Portugal.

SWEDEN
INDUO AB
 +46 8 659 43 00
 info@induo.com
www.induo.com

SWITZERLAND
SATEL SWITZERLAND - TUNCELLI SA
 +41 21 729 59 83
 ctuncelli@satelch.com
www.satelch.com

TAIWAN
ENVIRONMENTAL
SCIENCE & ENG'N CORP.
 +886 2 2963 4300
 daniel@esne.com.tw

www.esne.com.tw

THAILAND
 See South East Asia

TURKEY
BILKO AS
 +90 212 563 0000
 bilko@bilko.com.tr
www.sateltr.com

UKRAINE
PE "STC NEW TECHNOLOGIES"
 +38 044 499 7715
 satel@ntech.kiev.ua
www.ntech.com.ua

UNITED KINGDOM
SADERET LTD
 +44 1624 880366
 sales@saderet.co.uk
www.saderet.co.uk

XL SYSTEMS LTD
 +44 1883 622 778
 sales@xls.co.uk
www.xls.co.uk

UNITED STATES
ONYX NETWORKS TEXAS LLC
 +1 832 924 0125
 info@onyxnetworks.us
www.onyxnetworks.us

SATEL USA
 +1 408 973 1740
 info@satelusa.com
www.satelusa.com

URUGUAY
AEROMARINE S.A.
 +598 2 916 6456
 ar@aeromarine.com.uy
www.aeromarine.com.uy

VIETNAM
TRIEUHA TELECOMMUNICATIONS
 +84 4 3572 0699
 tuanav@trieuha.com
www.trieuha.com



EXPERT IN DESIGNING WIRELESS DATA TRANSFER NETWORKS

Whether you are new to wireless data radios, dealing with a complex setup, or facing other radio network challenges — we have got you covered.

Our Network Design Center will help you design a reliable, efficient, and trouble-free wireless data transfer network. Let's make your connectivity seamless!

Contact us

SATEL

SATEL, Meriniitynkatu 17
P.O.Box 142, FI-24101 Salo
FINLAND
Tel. +358 2 777 7800
info@satel.com

Follow us



DISCLAIMER

©2026 SATEL Oy. All rights to this catalogue are owned solely by SATEL Oy (referred to in this catalogue as SATEL). All rights reserved.

SATEL reserves the right to change the technical specifications or functions of its products, or to discontinue the manufacture of any of its products or to discontinue the support of any of its products, without any written announcement and urges its customers to ensure, that the information at their disposal is valid.

SATEL software and programs are delivered "as is". The manufacturer does not grant any kind of warranty including guarantees on suitability and applicability to a certain application. Under no circumstances is the manufacturer or the developer of a program responsible for any possible damages caused by the use of a program.